



Product Code:    A106-1  
Product Name:    WOOD AGER 1 GAL

Wood Finishers Depot   5215 Sjolander Raod   Baytown, TX 77521  
24-hour Emergency Phone:

800-424-9300

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near container (even empty) because product (even residue) may ignite explosively. Liquid and vapor states of this substance are dangerous fire hazards and moderate explosion hazards when exposed to heat or flame.

**FIREFIGHTING INSTRUCTIONS:**

Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bun coat, gloves, rubber boots and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

**6. ACCIDENTAL RELEASE MEASURES**

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways. Store in plastic containers. If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control agencies.

**7. HANDLING AND STORAGE**

**HANDLING:**

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid and/or solid), all hazard precautions given in this sheet must be observed.

**STORAGE:**

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**RESPIRATORY PROTECTION:**

PRIMARY ROUTES OF ENTRY: inhalation, skin contact, eyes, ingestion.

Use local exhaust as required to control vapor concentrations. Avoid prolonged or repeated breathing of vapors. If exposure exceeds TLV, use NIOSH-approved respirator to prevent overexposure.

**SKIN PROTECTION:**

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, butyl or nitrile. An apron should be worn to avoid skin contact.  
USE ACID RESISTANT CLOTHING TO MINIMIZE SKIN CONTACT.

**EYE PROTECTION:**

Wear splashproof goggles and face shield if there is a likelihood of contact with eyes.

**HYGENIC PRACTICES:**

Wash hands thoroughly before eating or using restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

Product Code: A106-1  
Product Name: WOOD AGER 1 GAL

Wood Finishers Depot 5215 Sjolander Road Baytown, TX 77521  
24-hour Emergency Phone: 800-424-9300

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: n/a  
MELTING POINT: N/A  
VAPOR PRESSURE: N/A  
VAPOR DENSITY: Heavier Than Air  
SOLUBILITY IN WATER: N/A  
SPECIFIC GRAVITY: 1.007  
COATING VOC LB/GL: 0.0 lb/gl  
COATING VOC GM/LTR: 0 g/l  
MATERIAL VOC LB/GL: 0.0 lb/gl  
MATERIAL VOC GM/LTR: 0 g/l  
% VOLATILE BY VOLUME: 99.625%  
EVAPORATION RATE: Faster than Butyl Acetate.  
WEIGHT PER GALLON: 8.382 lb/gl  
PH: N/A  
ODOR: N/A  
APPEARANCE: N/A

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:  
Stable Conditions to Avoid: High heat, sparks, flames, corrosive materials.  
INCOMPATIBILITY  
Materials to Avoid: Strong oxidizing agents, alkalines, strong mineral acids, ferrous metals.  
HAZARDOUS DECOMPOSITION PRODUCTS:  
Oxidation may produce carbon oxides.  
HAZARDOUS POLYMERIZATION:  
Will not occur.

11. TOXICOLOGICAL INFORMATION

CANCER INFORMATION:  
This product contains no reported carcinogens or suspected carcinogens.  
TERATOLOGY (BIRTH DEFECT) INFORMATION:  
This product contains no reported or suspected teratogens.  
REPRODUCTION INFORMATION:  
This product contains no reported or suspected mutagens.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:  
Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewer

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT NUMBER: UN2924  
Corrosive--by D.O.T. Standards

15. REGULATORY INFORMATION

HMIS HAZARD INDEX: 4=SEVERE, 3=SERIOUS, 2=MODERATE, 1=SLIGHT, 0=LEAST  
HEALTH: 3  
FLAMMABILITY: 0  
REACTIVITY: 1  
PERSONAL PROTECTION: I  
SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 3

