

CF-30 REFILLABLE BUTANE FUEL CELL**MATERIAL SAFETY DATA SHEET**

Complies with OSHA Hazard Communication
Standard 29 CPA 1910.1200

Identity: MINI BUTANE GAS, LIGHTER REFILL

SECTION I MANUFACTURER'S NAME & ADDRESS
--

SOLDER-IT, INC.
404 IRVINGTON STREET
PLEASANTVILLE, NY 10570

Emergency Telephone 1-800-255-3924 CHEM-TEL
Telephone # for information, 914-747-1092
Date Prepared: January 8, 2003
Signature of Preparer (optional)

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION
--

Hazardous Components (Specific Chemical Identity)	OSHA PEL-TWA	ACGIH TLV-TWA	Other Limits Recommended	Percentage (Optional)
N. BUTANE LIQUIFIED PETROLEUM GAS			800 PPM	

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS
--

Boiling Point (°F): 31.1°F	Specific Gravity: °F	
Vapor Pressure	Melting Points (H2O= 1)	NA
Vapor Density (Air = 1): 2	Evaporation Rate:	
Solubility In Water: VERY SLIGHTLY SOLUBLE	(Butyl Acetate = 1)	
Appearance Odor		

SECTION IV FIRE & EXPLOSION HAZARD DATA

Flash Point (°F): -76°F (CC) Flammability Limit: % BY VOLUME LEL 1.9 UEL 8.5

Extinguishing Media: Water, CO2

Special Firefighting Procedures: STOP FLOW OF GAS IF POSSIBLE
DOUSE WITH WATER OR SMOTHER WITH CO2

Unusual Fire & Explosion Hazards: FLAMMABLE VAPOR, HEAVIER THAN AIR

SOLDER-IT, INC.
404 IRVINGTON STREET
PLEASANTVILLE, NY 10570
PHONE 914-747-1092 FAX 914-741-1356

