

Product Code: GL1750-1
 Product Name: RAW SIENNA GLAZE (1 GAL)

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036
 24-hour Emergency Phone: 800-510-8510

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(SEE TOP OF PAGE)

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT/EXPOSURE LIMITS	CAS#
DMR 6% COBALT NAP-ALL	MIXTURE
MINERAL SPIRITS: ACGIH TLV100 ppm, OSHA PEL 100ppM	
ALIPHATIC PETROLEUM DISTILLATES	008052-41-3
TALC	14807-96-6
MINERAL SPIRITS	8052-41-3
MEDIUM ALIPHATIC NAPHTHA TWA 100ppm	64742-88-7
SOYA ALKYD	
SC150 PETROLEUM NAPHTHA NAPHTHALENE OSHA PEL: 10ppm, STEL 15 ppm, ACGIH 10ppm, STEL 15ppm TRIMETHYL BENZENE: OSHA PEL: 25ppm, ACGIH TLV: 25ppm	64742-94-5
ETHYLENE GLYCOL OSHA VPEL 100.000 PPM - TWA ACGIH TLV 1000.0000 PPM - TWA	107-21-1
METHANOL OSHA TWA PEL: 200ppm ACGIH TLV TWA 200ppm, STEL TLV 250ppm	67-56-1

3. HAZARDS IDENTIFICATION

FLAMMABLE IN A LIQUID STATE
 VAPOR CAUSES EYE BURNS AND SKIN IRRITATION

POTENTIAL HEALTH EFFECTS

SKIN: Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed
 INGESTION: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.
 INHALATION: High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs.

Date Printed: 6/29/2001

Page: 2

Product Code: GL1750-1
Product Name: RAW SIENNA GLAZE (1 GAL)

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036
24-hour Emergency Phone: 800-510-8510

4. FIRST AID MEASURES

EYES: Flush with luke warm water for a minimum of 15 minutes. Seek medical attention immediately.

SKIN: Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

INGESTION: Remove exposed individual to fresh air and assist breathing if necessary. Seek immediate medical attention.

INHALATION: Rinse mouth immediately. Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Contact physician or poison control center immediately.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASSIFICATION: CLASS 1B

LOWEST FLASH POINT: 40F METHOD:
DOT: FLAMMABLE LIQUID

FLAMMABLE LIMITS:
LOWER FLAMMABLE LIMIT: .9
UPPER FLAMMABLE LIMIT: 36

EXTINGUISHING MEDIA: Alcohol Foam, CO2, Dry Chemical.

The National Fire Protection Association Class B extinguisher is designed to extinguish NFPA Class 1B flammable liquid fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Close containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding torch on or near container (even empty) because product (even residue) may ignite explosively. Liquid vapor states of this substance are dangerous fire hazards and moderate explosion hazards when exposed to flame.

FIREFIGHTING INSTRUCTIONS: Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool containers to prevent pressure build up and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain spill if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways. If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and public safety control agencies.

7. HANDLING AND STORAGE

HANDLING: Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor and/or soiled), all hazard precautions given in this sheet must be observed. Wet down all used wiping rags with water in a covered metal container to prevent spontaneous combustion.

Product Code: GL1750-1
Product Name: RAW SIENNA GLAZE (1 GAL)

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036
24-hour Emergency Phone: 800-510-8510

STORAGE: Keep product containers cool, dry and away from sources of ignition. Use and store this product adequate ventilation. DO NOT SMOKE in or near storage areas

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: Use local exhaust as required to control vapors concentrations. Avoid prolonged or repeated breathing of vapors. If exposure exceeds TLV, use NIOSH-approved respirator to prevent overexposure.

SKIN PROTECTION: Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber neoprene, buna N or nitrile. An apron should be worn to avoid skin contact.

EYE PROTECTION: Wear splashproof goggles and face shield if there is a likelihood of contact with eyes.

HYGENIC PRACTICES: Wash hands thoroughly before eating or using restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 147F
MELTING POINT: N/A
VAPOR PRESSURE: N/A
VAPOR DENSITY: Heavier Than Air
SOLUBILITY IN WATER: N/A
SPECIFIC GRAVITY: 1.11
COATING VOC LB/GL: 4.29 lb/gl
COATING VOC GM/LTR: 514 g/l
MATERIAL VOC LB/GL: 4.23 lb/gl
MATERIAL VOC GM/LTR: 507 g/l
% VOLATILE BY VOLUME: 63.72%
EVAPORATION RATE: Faster than Butyl Acetate.
HAPS/GALLON: .
LBS HAPS/LBS SOLID: .
WEIGHT PER GALLON: 9.27 lb/gl
PH: N/A
ODOR: N/A
APPEARANCE: N/A

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable **Conditions to Avoid:** high heat, sparks, flames
INCOMPATIBILITYMaterials to Avoid: Strong oxidizing agents, strong alkalines, strong mineral acids
HAZARDOUS DECOMPOSITION PRODUCTS: Oxidation may produce carbon and nitrogen oxides.
HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

CANCER INFORMATION: This product contains no reported carcinogens or suspected carcinogens.
TERATOLOGY (BIRTH DEFECT) INFORMATION: This product contains no reported or suspected teratogens.
REPRODUCTION INFORMATION: This product contains no reported or suspected mutagens.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

M A T E R I A L S A F E T Y D A T A S H E E T

Date Printed: 6/29/2001

Page: 4

Product Code: GL1750-1
Product Name: RAW SIENNA GLAZE (1 GAL)

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036
24-hour Emergency Phone: 800-510-8510

DOT NUMBER: UN1263

15. REGULATORY INFORMATION

HMIS HAZARD INDEX: 4=SEVERE, 3=SERIOUS, 2=MODERATE, 1=SLIGHT, 0=LEAST

HEALTH: 2

FLAMMABILITY: 3

REACTIVITY: 0

PERSONAL PROTECTION: I

SECTION 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

* METHANOL

67-56-1

% BY WT
1

16. OTHER INFORMATION:

THE INFORMATION CONTAINED HEREIN IS INFORMATION RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCE BELIEVED TO BE RELIABLE. THIS DATA IS NOT TO BE TAKEN AS A WARRANTY OR REPRESENTATION FROM WHICH GEMINI INDUSTRIES, INC. ASSUMES LEGAL RESPONSIBILITY.