

M A T E R I A L   S A F E T Y   D A T A   S H E E T

Date Printed: 12/15/2004

Page:  
1

Product Code: AEROSOL TONER  
Product Name: AEROSOL TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036  
24-hour Emergency Phone: 800-510-8510

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(SEE TOP OF PAGE)

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT/EXPOSURE LIMITS</u>	<u>CAS#</u>
SUSPENSION ADDITIVE ACGIH-TLV: MINERAL SPIRITS, 100ppm, 1,2,4-TRIMETHYLBENZENE 25ppm OSHA PEL : MINERAL SPIRITS, 100ppm	MIXTURE
TOLUENE OSHA PEL: 200ppm ACGIH TLV 50ppm	108-88-3
PROPANE	74-98-6
N. BUTANE	106-97-8
ETHANOL OSHA: 1000 PPM PEL-TWA NIOSH: 1000 PPM PEL-TWA	64-17-5
ACETONE	67-64-1
ISOBUTYL ACETATE	110-19-0
ISOPROPANOL 400ppm TWA8 ACGIH, 983 mg/m3 TWA8 ACGIH 980mg/m3 TWA8 OSHA, 500ppM STEL OSHA	67-63-0
NITROCELLULOSE	9004-70-0
n-BUTYL ACETATE BUTYL ACETATE ACGIH 150ppm TWA, 200ppm STEL BUTYL ACETATE OSHA 150ppM TWA, 200ppM STEL	000123-86-4
n-BUTANOL OSHA PEL: 100ppm TWA ACGIH TLV 50ppm	71-36-3
PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6
ETHYLENE GLYCOL MONOBUTYL ETHER ACGIH 25ppm TWA OSHA 25ppm TWA	111-76-2
DIBUTYL ESTER DIBUTYL PHTHALATE: OSHA PEL 5.00mg/m3, ACGIH TLV 5.00mg/m3	84-74-2
DIMETHYL PHTHALATE	131-11-3
XYLENE	1330-20-7

M A T E R I A L   S A F E T Y   D A T A   S H E E T

Date Printed: 12/15/2004

Page:  
1

Product Code: AEROSOL TONER  
Product Name: AEROSOL TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036  
24-hour Emergency Phone: 800-510-8510

OSHA: 100 PPM PEL-TWA  
NIOSH: 100 PPM PEL-TWA

**3. HAZARDS IDENTIFICATION**

FLAMMABLE LIQUID UNDER PRESSURE  
VAPOR CAUSES EYE BURNS AND SKIN IRRITATION

**POTENTIAL HEALTH EFFECTS**

**SKIN:**

Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.

**INGESTION:**

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.

**INHALATION:**

High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs.

**4. FIRST AID MEASURES**

**EYES:**

Flush with luke warm water for a minimum of 15 minutes. Seek medical attention immediately.

**SKIN:**

Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

**INGESTION:**

Rinse mouth immediately. Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Contact physician or poison control center immediately.

**INHALATION:**

Remove exposed individual to fresh air and assist breathing if necessary. Seek immediate medical attention.

**5. FIRE FIGHTING MEASURES**

**FLAMMABLE CLASSIFICATION: CLASS 1B**

**LOWEST FLASH POINT: 40F**

**METHOD:**

**FLAMMABLE LIMITS:**

**LOWER FLAMMABLE LIMIT: 0**

**UPPER FLAMMABLE LIMIT: 12.7**

**EXTINGUISHING MEDIA: Alcohol Foam, CO2, Dry Chemical**

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Burning may produce oxides of nitrogen and carbon. Do not puncture or incinerate container. Exposure to heat or prolonged exposure to sun may cause container to burst. Do not expose to heat or store at temperatures above 120 degrees F. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, sparks, heaters, smoking, electrical motors or static discharge distant from handling point.

M A T E R I A L   S A F E T Y   D A T A   S H E E T

Date Printed: 12/15/2004

Page:  
1

Product Code: AEROSOL TONER  
Product Name: AEROSOL TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036  
24-hour Emergency Phone: 800-510-8510

**FIREFIGHTING INSTRUCTIONS:**

**6. ACCIDENTAL RELEASE MEASURES**

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways. If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control agencies.

**7. HANDLING AND STORAGE**

**HANDLING:**

Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid and/or solid), all hazard precautions given in this sheet must be observed.

**STORAGE:**

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**RESPIRATORY PROTECTION:**

PRIMARY ROUTES OF ENTRY: inhalation, skin contact, eyes, ingestion.

Use local exhaust as required to control vapor concentrations. Avoid prolonged or repeated breathing of vapors. If exposure exceeds TLV, use NIOSH-approved respirator to prevent overexposure.

**SKIN PROTECTION:**

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact.

**EYE PROTECTION:**

Wear splashproof goggles and face shield if there is a likelihood of contact with eyes.

**HYGENIC PRACTICES:**

Wash hands thoroughly before eating or using restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

BOILING POINT: 231F  
MELTING POINT: N/A  
VAPOR PRESSURE: N/A  
VAPOR DENSITY: Heavier Than Air  
SOLUBILITY IN WATER: N/A  
SPECIFIC GRAVITY: .773  
COATING VOC LB/GL: 1.7536 lb/gl  
COATING VOC GM/LTR: 210 g/l  
MATERIAL VOC LB/GL: 1.7536 lb/gl  
MATERIAL VOC GM/LTR: 210 g/l  
% VOLATILE BY VOLUME: 38.969%

M A T E R I A L   S A F E T Y   D A T A   S H E E T

Date Printed: 12/15/2004

Page:  
1

Product Code: AEROSOL TONER  
Product Name: AEROSOL TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036  
24-hour Emergency Phone: 800-510-8510

EVAPORATION RATE: Faster than Butyl Acetate.  
WEIGHT PER GALLON: 6.436 lb/gal  
PH: N/A  
ODOR: N/A  
APPEARANCE: N/A

**10. STABILITY AND REACTIVITY**

**CHEMICAL STABILITY:**

Stable Conditions to Avoid: high heat, sparks, flames

**INCOMPATIBILITY**

Materials to Avoid: Strong oxidizing agents, strong alkalines, strong mineral acids.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Oxidation may produce carbon and nitrogen oxides.

**HAZARDOUS POLYMERIZATION:**

Will not occur.

**11. TOXICOLOGICAL INFORMATION**

**CANCER INFORMATION:**

This product contains no reported carcinogens or suspected carcinogens. This product contains no reportable hazardous ingredients. This Material Safety Data Sheet contains information on good industrial practice for safe handling of all industrial chemicals.

**TERATOLOGY (BIRTH DEFECT) INFORMATION:**

This product contains no reported or suspected teratogens.

**REPRODUCTION INFORMATION:**

Toluene is a chemical known to the state of California to cause birth defect or other reproductive harm.

**12. ECOLOGICAL INFORMATION**

**ECOLOGICAL INFORMATION:**

**13. DISPOSAL CONSIDERATIONS**

Dispose in accordance with local, state and federal regulations.

**14. TRANSPORT INFORMATION**

AEROSOLS, FLAMMABLE, 2.1, UN1950

**15. REGULATORY INFORMATION**

HMIS HAZARD INDEX: 4=SEVERE, 3=SERIOUS, 2=MODERATE, 1=SLIGHT, 0=LEAST

HEALTH: 2

FLAMMABILITY: 4

REACTIVITY: 0

PERSONAL PROTECTION: J

SECTION 313:

**% BY WT**

* TOLUENE	108-88-3	20
* n-BUTANOL	71-36-3	3
* ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	2
* DIBUTYL ESTER	84-74-2	2
* DIMETHYL PHTHALATE	131-11-3	
* XYLENE	1330-20-7	

**16. DISCLAIMER:**

The following supercedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products

M A T E R I A L   S A F E T Y   D A T A   S H E E T

Date Printed: 12/15/2004

Page:  
1

Product Code: AEROSOL TONER  
Product Name: AEROSOL TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036  
24-hour Emergency Phone: 800-510-8510

should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS.

TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.

M A T E R I A L   S A F E T Y   D A T A   S H E E T

Date Printed: 12/15/2004

Page:  
1

**Product Code:** AEROSOL TONER

**Product Name:** AEROSOL TONER

**GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036**

**24-hour Emergency Phone: 800-510-8510**