

Product Code: LA186
 Product Name: ANTIQUE WHITE LACQUER TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036
 24-hour Emergency Phone: 800-510-8510

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(SEE TOP OF PAGE)

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT/EXPOSURE LIMITS	CAS#
BURNT UMBER 525	MIXTURE
ACGIH-TLV: IRON (III)OXIDE5mg/m3, MANGANESE OXIDE .2 mg/m3, QUARTZ .1 mg/M3	
TOLUENE 50ppm	
OSHA-PEL IRON (III) OXIDE 10mg/m3, QUARTZ .1 mg/m3, TOLUENE 200ppm	
OSHA-STEL TOLUENE300ppm	
TOLUENE	108-88-3
OSHA PEL: 200ppm	
ACGIH TLV 50ppm	
PROPANE	74-98-6
N. BUTANE	106-97-8
ETHANOL	64-17-5
OSHA: 1000 PPM PEL-TWA	
NIOSH: 1000 PPM PEL-TWA	
ACETONE	67-64-1
OSHA VPEL 750 ppm TWA	
OSHA VPEL 1000 ppm STEL	
ACGIH TLV 500ppm TWA	
ACGIH TLV 750 ppm STEL	
ISOBUTYL ACETATE	110-19-0
ISOPROPANOL	67-63-0
400 ppm TWA8 ACGIH	
980mg/m3 TWA8 OSHA	
NITROCELLULOSE	9004-70-0
n-BUTYL ACETATE	000123-86-4
BUTYL ACETATE ACGIH 150ppm TWA, 200ppm STEL	
BUTYL ACETATE OSHA 150ppm TWA, 200ppm STEL	
n-BUTANOL	71-36-3
OSHA PEL: 100ppm TWA	
ACGIH TLV 50ppm	
PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2
ACGIH 25ppm TWA	
OSHA 25ppm TWA	
DIBUTYL ESTER	84-74-2

Product Code: LA186
Product Name: ANTIQUE WHITE LACQUER TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036
24-hour Emergency Phone: 800-510-8510

DIBUTYL PHTHALATE: OSHA PEL 5.00mg/m3, ACGIH TLV 5.00mg/m3
DIMETHYL PHTHALATE 131-11-3

XYLENE 1330-20-7
OSHA: 100 PPM PEL-TWA
NIOSH: 100 PPM PEL-TWA

3. HAZARDS IDENTIFICATION

FLAMMABLE LIQUID UNDER PRESSURE
VAPOR CAUSES EYE BURNS AND SKIN IRRITATION

POTENTIAL HEALTH EFFECTS

SKIN:

Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.

INGESTION:

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.

INHALATION:

High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs.

4. FIRST AID MEASURES

EYES:

Flush with luke warm water for a minimum of 15 minutes. Seek medical attention immediately.

SKIN:

Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

INGESTION:

Rinse mouth immediately. Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Contact physician or poison control center immediately.

INHALATION:

Remove exposed individual to fresh air and assist breathing if necessary. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASSIFICATION: CLASS 1B

LOWEST FLASH POINT: 40F

METHOD:

FLAMMABLE LIMITS:

LOWER FLAMMABLE LIMIT: 0

UPPER FLAMMABLE LIMIT: 12.8

EXTINGUISHING MEDIA: Alcohol Foam, CO2, Dry Chemical

UNUSUAL FIRE AND EXPLOSION HAZARDS

Burning may produce oxides of nitrogen and carbon. Do not puncture or incinerate container.

Product Code: LA186
Product Name: ANTIQUE WHITE LACQUER TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036
24-hour Emergency Phone: 800-510-8510

Exposure to heat or prolonged exposure to sun may cause container to burst. Do not expose to heat or store at temperatures above 120 degrees F. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, sparks, heaters, smoking, electrical motors or static discharge distant from handling point.

FIREFIGHTING INSTRUCTIONS:

6. ACCIDENTAL RELEASE MEASURES

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways. If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control agencies.

7. HANDLING AND STORAGE

HANDLING:

Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid and/or solid), all hazard precautions given in this sheet must be observed.

STORAGE:

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

PRIMARY ROUTES OF ENTRY: inhalation, skin contact, eyes, ingestion.

Use local exhaust as required to control vapor concentrations. Avoid prolonged or repeated breathing of vapors. If exposure exceeds TLV, use NIOSH-approved respirator to prevent overexposure.

SKIN PROTECTION:

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, butyl or nitrile. An apron should be worn to avoid skin contact.

EYE PROTECTION:

Wear splashproof goggles and face shield if there is a likelihood of contact with eyes.

HYGENIC PRACTICES:

Wash hands thoroughly before eating or using restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 133F
MELTING POINT: N/A
VAPOR PRESSURE: N/A
VAPOR DENSITY: Heavier Than Air
SOLUBILITY IN WATER: N/A
SPECIFIC GRAVITY: .771
COATING VOC LB/GL: 1.7493 lb/gl
COATING VOC GM/LTR: 210 g/l

Product Code: LA186
 Product Name: ANTIQUE WHITE LACQUER TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036
 24-hour Emergency Phone: 800-510-8510

MATERIAL VOC LB/GL: 1.7493 lb/gl
 MATERIAL VOC GM/LTR: 210 g/l
 % VOLATILE BY VOLUME: 38.874%
 EVAPORATION RATE: Faster than Butyl Acetate.
 WEIGHT PER GALLON: 6.42 lb/gl
 PH: N/A
 ODOR: N/A
 APPEARANCE: N/A

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:

Stable Conditions to Avoid: high heat, sparks, flames

INCOMPATIBILITY

Materials to Avoid: Strong oxidizing agents, strong alkalines, strong mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxidation may produce carbon and nitrogen oxides.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

CANCER INFORMATION:

This product contains no reported carcinogens or suspected carcinogens. This product contains no reportable hazardous ingredients. This Material Safety Data Sheet contains information on good industrial practice for safe handling of all industrial chemicals.

TERATOLOGY (BIRTH DEFECT) INFORMATION:

This product contains no reported or suspected teratogens.

REPRODUCTION INFORMATION:

Toluene is a chemical known to the state of California to cause birth defect or other reproductive har

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

AEROSOLS, FLAMMABLE, 2.1, UN1950

15. REGULATORY INFORMATION

HMIS HAZARD INDEX: 4=SEVERE, 3=SERIOUS, 2=MODERATE, 1=SLIGHT, 0=LEAST

HEALTH: 2

FLAMMABILITY: 4

REACTIVITY: 0

PERSONAL PROTECTION: J

SECTION 313:

% BY WT

* BURNT UMBER 525	MIXTURE	117
* TOLUENE	108-88-3	20
* n-BUTANOL	71-36-3	3
* ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	2
* DIBUTYL ESTER	84-74-2	2
* DIMETHYL PHTHALATE	131-11-3	
* XYLENE	1330-20-7	

Product Code: LA186
Product Name: ANTIQUE WHITE LACQUER TONER

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036

24-hour Emergency Phone: 800-510-8510

16. DISCLAIMER:

The following supercedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herin is believed to be reliable. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRENTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS.

TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.