

Date Printed: 6/28/2001

Page: 1

Product Code: PL1010-1

Product Name: One Minute Touch UP ( 1 GAL.)

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036

24-hour Emergency Phone: 800-510-8510

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

(SEE TOP OF PAGE)

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

COMPONENT/EXPOSURE LIMITS	CAS#
DUPLICATING FLUID	MIXTURE
ETHANOL: TWA OSHA 1000 ppm, TLV 1000ppm	
N-PROPYL ACETATE: TWA OSHA 200ppm, TLV ACGIH 200ppm	
ISOPROPANOL: 400 ppm, 400ppm	
ETHANOL	64-17-5
ACETONE	67-64-1
OSHA VPEL 750 ppm TWA	
OSHA VPEL 1000 ppm STEL	
ACGIH TLV 500ppm TWA	
ACGIH TLV 750 ppm STEL	
n-PROPYL ACETATE	109-60-4
ISOPROPANOL	67-63-0
400ppm TWA8 ACGIH, 983 mg/m3 TWA8 ACGIH	
980mg/m3 TWA8 OSHA, 500ppm STEL OSHA	

**3. HAZARDS IDENTIFICATION**

FLAMMABLE IN A LIQUID STATE

HIGH VAPOR CONCENTRATIONS MAY CAUSE MILD EYE AND SKIN IRRITATION.

**POTENTIAL HEALTH EFFECTS**

SKIN: Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed

INGESTION: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.

INHALATION: High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs.

**4. FIRST AID MEASURES**

EYES: Flush with luke warm water for a minimum of 15 minutes. Seek medical attention immediately.

SKIN: Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

INGESTION: Remove exposed individual to fresh air and assist breathing if necessary. Seek immediate medical attention.

INHALATION: Rinse mouth immediately. Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Contact physician or poison control center immediately.

**5. FIRE FIGHTING MEASURES**

Date Printed: 6/28/2001

Page: 2

Product Code: PL1010-1  
Product Name: One Minute Touch UP ( 1 GAL.)

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036  
24-hour Emergency Phone: 800-510-8510

**FLAMMABLE CLASSIFICATION: CLASS 1B**

LOWEST FLASH POINT: 40F    METHOD: TCC

DOT: FLAMMABLE LIQUID

**FLAMMABLE LIMITS:**

LOWER FLAMMABLE LIMIT: 2.6

UPPER FLAMMABLE LIMIT: 12.8

EXTINGUISHING MEDIA: Alcohol Foam, CO2, Dry Chemical.

The National Fire Protection Association Class B extinguisher is designed to extinguish NFPA Class 1B flammable liquid fires.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use a welding cutting torch on or near container (even empty) because product (even residue) may ignite explosively. The liquid and vapor states of this substance are dangerous fire hazards and moderate explosion hazards when exposed to heat or flame.

**FIREFIGHTING INSTRUCTIONS:** Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat. When water is used, fog nozzles are preferable.

**6. ACCIDENTAL RELEASE MEASURES**

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain spill if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewers, or waterways. If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and environmental control agencies.

**7. HANDLING AND STORAGE**

**HANDLING:** Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor and/or solid), all hazard precautions given in this sheet must be observed.

**STORAGE:** Keep product containers cool, dry and away from sources of ignition. Use and store this product in areas with adequate ventilation. DO NOT SMOKE in or near storage areas

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**RESPIRATORY PROTECTION:** Use local exhaust as required to control vapor concentrations. Avoid prolonged or repeated breathing of vapors. If exposure exceeds TLV, use NIOSH-approved respirator to prevent overexposure.

**SKIN PROTECTION:** Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact.

**EYE PROTECTION:** Wear splashproof goggles and face shield if there is a likelihood of contact with eyes.

Date Printed: 6/28/2001

Page: 3

Product Code: PL1010-1  
Product Name: One Minute Touch UP ( 1 GAL.)

GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036  
24-hour Emergency Phone: 800-510-8510

HYGENIC PRACTICES: Wash hands thoroughly before eating or using restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 133F  
MELTING POINT: N/A  
VAPOR PRESSURE: N/A  
VAPOR DENSITY: Heavier Than Air  
SOLUBILITY IN WATER: N/A  
SPECIFIC GRAVITY: .82  
COATING VOC LB/GL: . lb/gl  
COATING VOC GM/LTR: g/l  
MATERIAL VOC LB/GL: . lb/gl  
MATERIAL VOC GM/LTR: g/l  
% VOLATILE BY VOLUME: .%  
EVAPORATION RATE: Faster than Butyl Acetate.  
HAPS/GALLON: .  
LBS HAPS/LBS SOLID: .  
WEIGHT PER GALLON: 6.87 lb/gl  
PH: N/A  
ODOR: N/A  
APPEARANCE: N/A

## 10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable      Conditions to Avoid: high heat, sparks, flames.  
INCOMPATIBILITY Materials to Avoid: Strong oxidizing agents, strong alkalines, strong mineral acids  
HAZARDOUS DECOMPOSITION PRODUCTS: Oxidation may produce carbon and nitrogen oxides.  
HAZARDOUS POLYMERIZATION: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

CANCER INFORMATION: This product contains no reported carcinogens or suspected carcinogens.  
TERATOLOGY (BIRTH DEFECT) INFORMATION: This product contains no reported or suspected teratogens.  
REPRODUCTION INFORMATION:

## 12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers.

## 13. DISPOSAL CONSIDERATIONS

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, cou federal regulations.

## 14. TRANSPORT INFORMATION

DOT NUMBER: UN1263

## 15. REGULATORY INFORMATION

HMIS HAZARD INDEX: 4=SEVERE, 3=SERIOUS, 2=MODERATE, 1=SLIGHT, 0=LEAST  
HEALTH: 2  
FLAMMABILITY: 3  
REACTIVITY: 0  
PERSONAL PROTECTION: I

SECTION 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

M A T E R I A L   S A F E T Y   D A T A   S H E E T

Date Printed: 6/28/2001

Page: 4

---

**Product Code:** PL1010-1

**Product Name:** One Minute Touch UP ( 1 GAL.)

**GEMINI INDUSTRIES, INC., 2300 HOLLOWAY DRIVE, EL RENO, OK 73036**

**24-hour Emergency Phone: 800-510-8510**

---

16. OTHER INFORMATION:

THE INFORMATION CONTAINED HEREIN IS INFORMATION RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCE BELIEVED TO BE RELIABLE. THIS DATA IS NOT TO BE TAKEN AS A WARRANTY OR REPRESENTATION FROM WHICH GEMINI INDUSTRIES, INC. ASSUMES LEGAL RESPONSIBILITY.